

Modelo		LDN 36 INV PT	
Power Supply		V/Ph/Hz	380-415/3/50
Cooling	Potencia Frigorifica	Btu/hr	41000
	Consumo Electrico	w	4100
	Corriente	amp	9
	SEER	Btu/h*W	16
Heating	Potencia Frigorifica	Btu/hr	47800
	Consumo Electrico	w	4100
	Corriente	amp	8,2
	HSPF	Btu/h*W	9
Max. Potencia Electrica		w	4900
Max. Corriente		amp	13,5
Compressor type			Inverter Rotary
Compressor brand			GREE
Drain pipe		mm	DN25
Piping Liquid side		mm	9,52
		pulg	3/8
Piping Gas side		mm	15,875
		pulg	5/8
Max. Pipe lenght		m	65
Max. High drop		m	30
Application area		m2	40 - 70
INDOOR			
Indoor air flow (Hi/Med/Lo)		m3/h	1600/1500/1400/1200
Indoor noise level (Hi/Med/Lo)		dB(A)	50/49/48
Dimensiones (WxHxD)		mm	1200x665x235
Dimensiones de paquete (WxHxD)		mm	1363x770x300
Net / Gross weight		kg	33/39
OUTDOOR			
Indoor air flow		m3/h	5900
Indoor noise level		dB(A)	58
Dimensiones (WxHxD)		mm	940x460x820
Dimensiones de paquete (WxHxD)		mm	1083x573x973
Net / Gross weight		kg	90/102
Refrigerant type / Quantity		g	R410/3400

<i>Modelo</i>		<i>LDN 48 INV PT</i>	
Power Supply		V/Ph/Hz	380-415/3/50
Cooling	Potencia Frigorifica	Btu/hr	47800
	Consumo Electrico	w	5200
	Corriente	amp	11
	SEER	Btu/h*W	16
Heating	Potencia Frigorifica	Btu/hr	51200
	Consumo Electrico	w	4400
	Corriente	amp	10
	HSPF	Btu/h*W	9
Max. Potencia Electrica		w	5900
Max. Corriente		amp	17
Compressor type			Inverter Rotary
Compressor brand			GREE
Drain pipe		mm	DN25
Piping Liquid side		mm	9,52
		pulg	3/8
Piping Gas side		mm	15,875
		pulg	5/8
Max. Pipe lenght		m	75
Max. High drop		m	30
Application area		m2	55 - 95
INDOOR			
Indoor air flow (Hi/Med/Lo)		m3/h	2200/2000/1800/1500
Indoor noise level (Hi/Med/Lo)		dB(A)	53/52/51
Dimensiones (WxHxD)		mm	1570×665×235
Dimensiones de paquete (WxHxD)		mm	1729×770×300
Net / Gross weight		kg	40/47
OUTDOOR			
Indoor air flow		m3/h	5900
Indoor noise level		dB(A)	59
Dimensiones (WxHxD)		mm	940×460×820
Dimensiones de paquete (WxHxD)		mm	1083×573×973
Net / Gross weight		kg	96/108
Refrigerant type / Quantity		g	R410A/3,7
Design pressure		Mpa	4.5/1.2

Modelo		LDN 60 INV PT	
Power Supply		V/Ph/Hz	380-415/3/50
Cooling	Potencia Frigorifica	Btu/hr	52500
	Consumo Electrico	w	5200
	Corriente	amp	13
	SEER	Btu/h*W	16
Heating	Potencia Frigorifica	Btu/hr	58000
	Consumo Electrico	w	4800
	Corriente	amp	11
	HSPF	Btu/h*W	9
Max. Potencia Electrica		w	6300
Max. Corriente		amp	17
Compressor type		Rotativo / Scroll	
Compressor brand		GREE	
Drain pipe		mm	DN25
Piping Liquid side		mm	9,52
		pulg	3/8
Piping Gas side		mm	15,875
		pulg	5/8
Max. Pipe lenght		m	50
Max. High drop		m	30
Application area		m2	60 - 105
INDOOR			
Indoor air flow (Hi/Med/Lo)		m3/h	2300/2200/1900/1600
Indoor noise level (Hi/Med/Lo)		dB(A)	53/52/51
Dimensiones (WxHxD)		mm	1570x665x235
Dimensiones de paquete (WxHxD)		mm	1729x770x300
Net / Gross weight		kg	42/49
OUTDOOR			
Indoor air flow		m3/h	5900
Indoor noise level		dB(A)	60
Dimensiones (WxHxD)		mm	940x460x820
Dimensiones de paquete (WxHxD)		mm	1083x573x973
Net / Gross weight		kg	103/114
Refrigerant type / Quantity		g	R410A/3800
Design pressure		Mpa	4.5/1.2